ICI T-Cam 32 S-Series


The ICI T-Cam 32 S-Series is a very affordable 32 x 31 pixel resolution hand held thermal imaging camera. It weighs only 494g and measures 125mm x 58mm x 205mm. It's color TFT LCD screen measures 2.2" and has a 320 x 240px resolution to view images and to locate hot spots on the job. All your images are saved in JPEG format and are stored inside of a MicroSD memory card located inside the handle. And the Hot Spot/Cold Spot tracking feature helps you find the areas of concern very quickly.

Features

- Uncooled Detector (hyper thin pyroelectric ceramic)
- 32x31 Pixel Array
- 9Hz (S-Series)
- USB 2.0 for Power/Data
- Visual Camera
- Dual Laser Targeting
- Li-ION Rechargable Battery
- Meterbox IRTP & Cloud Service

Options & Accessories

- Hard Transport Case
- 3.7V Li-ION Battery
- USB Cable
- MicroSD Card 8GB
- Tripod
- TEKA AC Adapter w/USB
- 250V Adapter



Infrared Cameras Inc

2105 W. Cardinal Dr. Beaumont, TX 77705 (409) 861-0788 Phone (866) 861-0788 Toll Free

Applications

- · Insulation Inspection
- Scientific Research
- Predictive Maintenance
- Reliability Engineering
- Roof Insections
- HVAC
- Electrical

Specifications

- 20 x 20 FOV
- 8μm-14μm Spectral Response
- 14 bit Dynamic Range
- <150 mk Thermal Sensitivity</p>
- -20C to 180C Object Temp Range

ICI

- +/- 2C Accuracy
- 2G Shock/Vibration
- 125x58x205 without lens (HxWxD +/- .5mm)
- 494 Grams without lens

